

Handheld interventional ultrasound/photoacoustic puncture needle navigation based on deep learning segmentation: supplement

**XIANGWEI LIN,^{1,*} HONGJI SHI,¹ XIAOZHOU FAN,² JIAXIN WANG,³
ZHENYU FU,¹ YUQING CHEN,¹ SIPING CHEN,¹ XIN CHEN,¹ AND MIAN
CHEN^{1,4}**

¹*School of Biomedical Engineering, Shenzhen University, 1066 Xueyuan Ave, Shenzhen 518057, China*

²*Department of Ultrasound, Air Force Medical Center, Air Force Medical University, 30 Fucheng Road, Beijing 100142, China*

³*School of Chinese Materia Medica, Beijing University of Chinese Medicine, 11 Huandong Road, Beijing 102488, China*

⁴*mian.chen@szu.edu.cn*

**lin_xiangwei@yeah.net*

This supplement published with Optica Publishing Group on 26 October 2023 by The Authors under the terms of the [Creative Commons Attribution 4.0 License](#) in the format provided by the authors and unedited. Further distribution of this work must maintain attribution to the author(s) and the published article's title, journal citation, and DOI.

Supplement DOI: <https://doi.org/10.6084/m9.figshare.24420937>

Parent Article DOI: <https://doi.org/10.1364/BOE.504999>

Handheld interventional ultrasound/photoacoustic puncture needle navigation based on deep learning segmentation

XIANGWEI LIN, ^{1,*} HONGJI SHI, ¹ XIAOZHOU FAN, ² JIAXIN WANG, ³ ZHENYU FU, ¹ YUQING CHEN, ¹ SIPING CHEN, ¹ XIN CHEN, ¹ MIAN CHEN ^{1,*}

¹ School of Biomedical Engineering, Shenzhen University, 1066 Xueyuan Ave, Shenzhen, 518057, China

² Department of Ultrasound, Air Force Medical Center, Air Force Medical University, 30 Fucheng Road, Beijing 100142, China

³ School of Chinese Materia Medica, Beijing University of Chinese Medicine, 11 Huandong Road, Beijing 102488, China.

* lin_xiangwei@yeah.net, * mian.chen@szu.edu.cn




Fig. S1. Attention gate mechanism in the U-Net++ architecture.

Explanation to Fig. S1: In the spatial attention module, the input feature tensor was first concatenated through global average pooling and global maximum pooling on the channel, followed by a 7×7 convolution and the sigmoid activation function to get a weight graph with one channel. After multiplying the weight graph with the original input tensor, a characteristic tensor was finally output. In the channel attention module, the feature tensor output by the spatial attention module was first obtained through global average pooling and global maximum pooling to obtain two feature weight sequences. Then these two weight sequences were added after one convolution and sigmoid activation function. Multiplying the weight sequence with the output of the spatial attention module, finally the feature tensor of the same type as the feature tensor of the spatial attention module was obtained.




Fig. S2. Dual-modality needle shaft-tip compensation in the representative cases.